SLITTING LINE & CUT TO LENGTH LINE

By SRET Equipment





SRET Equipment provides complete coil processing systems for slitting line and cut to length meet your needs, that includes high speed and high thickness. Thanks for SRET Equipment guarantee an excellent quality

Slitting Line



Model No.	Coil Thickness (mm)	Coil Width (mm)	Coil Weight (t)	Finished Strip Width (mm)	No. of Slitting Strips	Line Speed (m/min.)
SL6x2000	1-6	900 - 2,000	30	≥50	≤10	Max. 50
SL8x2000	2-8	900 - 2,000	30	≥70	≤8	Max. 40
SL12x2200	3 - 12	900 - 2,200	35	≥80	≤7	Max. 30
SL16x2200	4-16	900 - 2,200	35	≥100	≤5	Max. 25
SL20x2200	5 - 20	900 - 2,200	35	≥150	≤3	Max. 20

High Speed Slitting Line

Model No.	Coil Thickness (mm)	Coil Width (mm)	Coil Weight (t)	No. of Slitting Strips	Line Speed (m/min.)
SL-H-6x2000	0.3 - 3.0	800 - 2,000	20	≤30	Max. 180



Leveler



Model No.	Coil Thickness (mm)	Coil Width (mm)	No. of Rollers	Roller Dia. (mm)	Line Speed (m/min.)	Leveling Tolerance (mm/m²)
LR6x2000	1-6	900 - 2,000	15	Ø 140	Max. 15	≤±2
LR8x2000	2-8	900 - 2,000	13	Ø 160	Max. 15	≤±2
LR12x2200	3 - 12	900 - 2,200	11	Ø 180	Max. 12	≤±2
LR16x2200	4-16	900 - 2,200	11	Ø 200	Max. 12	≤±2
LR20x2200	6-20	900 - 2,200	9	Ø 230	Max. 8	≤±2
LR25x2500	8-25	900 - 2,500	9	Ø 260	Max. 8	≤±2
LR32x3500	9-32	1,000 - 3,500	9	Ø 300	Max. 6	≤±2
LR40x4000	10 - 40	1,000 - 4,000	9	Ø 355	Max. 6	≤±2
LR50x4000	15 - 50	1,000 - 4,000	9	Ø 450	Max. 6	≤±2

th line. Depending on your applications we can offer you the best appropriate solutions to rour engineering experience and great management of manufacturing, while competitive prices to meet your budget.

Model No.	Coil Thickness (mm)	Coil Width (mm)	Coil Weight (t)	Cut Length (mm)	Length Tolerance (mm)	Line Speed (m/min.)
CTL6x2000	1-6	900 - 2,000	30	1,000 - 6,000	≤±1	Max. 28
CTL8x2000	2-8	900 - 2,000	30	1,000 - 8,000	≤±1	Max. 28
CTL12x2200	3 - 12	900 - 2,200	35	2,000 - 12,000	≤±1	Max. 25
CTL16x2200	4 - 16	900 - 2,200	35	2,000 - 12,000	≤±1	Max. 25
CTL20x2200	6 - 20	900 - 2,200	35	2,000 - 12,000	≤±1	Max. 18

35

2,000 - 12,000

≤±1

Cut To Length Line



High Speed Cut To Length Line

CTL25x2500



8-25

900 - 2,500

Model No.	Coil Thickness (mm)	Coil Width (mm)	Coil Weight (t)	Cut Length (mm)	Length Tolerance (mm)	Line Speed (m/min.)
CTL-H-3x2000	0.3 - 3	800 - 2,000	20	300 - 4,000	≤±0.3	Max. 80
CTL-H-6x2000	1-6	900 - 2,000	30	1,000 - 6,000	≤±0.5	Max. 60

Max. 18

Stainless Steel Cut To Length Line

Model No.	Coil Thickness (mm)	Coil Width (mm)	Coil Weight (t)	Cut Length (mm)	Length Tolerance (mm)	Line Speed (m/min.)
CTL-S-6x2000	1-6	800 - 2,000	30	1,000 - 6,000	≤±0.5	Max. 60
CTL-S-8x2000	2-8	800 - 2,000	30	1,000 - 8,000	≤±1	Max. 28
CTL-S-12x2200	3 - 12	800 - 2,200	35	1,000 - 10,000	≤±1	Max. 25
CTL-S-16x2200	4 - 16	800 - 2,200	35	1,000 - 12,000	≤±1	Max. 25





SRET Equipment's China Headquarters

Shenyang SRET Equipment Co., Ltd

No. 17-11-2-2 Wensu Street, HunNan District, Shenyang, Liaoning Province, P.R. China 110171 Tel: +86 - 24 - 24502154, Fax: +86 - 24 - 24538186 Email: customer@sret-equipment.com

SRET Equipment's International Business Division

TrustMach International Inc.

4145 North Service Road, Suite 200
Burlington, Ontario, Canada L7L 6A3
Tel: +1-905-847-9853, Fax: +1-905-847-9853
Email: customer@sret-equipment.com